



HYDRO GUARD 2000



- ◆ ADHERES TO ALL COMMON SURFACES
- ◆ IAPMO APPROVED
- ◆ WATER AND VAPOR PROOF
- ◆ ANTI-FRACTURE PROTECTION UP TO 1/8" (3 MM)
- ◆ EXCEEDS ANSI A118.10 AND A118.12



HYDRO GUARD 2000



Merkrete Hydro Guard 2000 is a heavy-duty, thin, load-bearing membrane composed of a modified elastomeric copolymer. With excellent elongation properties and exceptional strength, Hydro Guard 2000 provides a 100% waterproof membrane coat with crack isolation protection, limiting the transfer of substrate cracks to the finished overlay. The membrane is installed in a liquid state and can be applied to practically any form or irregular shape (e.g., base flashings, parapets, walls, etc.).

STANDARDS:

- Exceeds ANSI A118.10 and A118.12
- IAPMO approved

USES:

- Interior and exterior
- Swimming pools, fountains and water features
- Shower pans, stalls and tubs surrounds
- Industrial, commercial and residential bathrooms and laundries
- Spas and hot tubs
- Kitchens and food processing areas
- Terraces and balconies over unoccupied spaces
- Countertops and façades

SUITABLE SUBSTRATES:

- Brick masonry
- Cement backer board¹
- Cement mortar beds
- Cement plaster
- Cement terrazzo
- Ceramic tile and stone
- Concrete
- Concrete masonry
- Exterior-grade plywood²
- Gypsum wallboard²
- Gypsum mortar bed³
- Oriented strand board²

¹ Consult cement backer board manufacturer for installation recommendations and to verify acceptability for exterior use.

² Interior use only.

³ Requires use of 101 Overspray Primer

APPROXIMATE COVERAGE:

- 2-gallon unit: 100 sq. ft.
- 5-gallon unit: 250 sq. ft.

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424

ORDERING INFORMATION

Item No.	Size
1797	2 Gal
1798	5 Gal