



PROGROUT PLUS



Merkrete's ProGrout Plus high-performance grout features innovative, patented DUSTLESS Technology (DLT), producing significantly less dust than ordinary thinsets to promote cleaner working conditions and reduce mess. It is creamier and easier to spread.

- ◆ **POLYMER FORTIFIED FOR HARD, DURABLE, PROFESSIONAL RESULTS**
- ◆ **STAIN RESISTANT, COLOR CONSISTENT AND EFFLORESCENCE FREE**
- ◆ **FOR 1/16" (1.5 MM) TO 1/2" (13 MM) GROUT JOINTS**
- ◆ **EASY MIXING — JUST ADD WATER; NO ADDITIVES REQUIRED**
- ◆ **EXCEEDS ANSI A118.7**





PROGROUT PLUS™



ProGrout Plus is a high-performance, fast-setting, DUSTLESS, color-consistent and efflorescence-free grout providing hard, durable grout joints. ProGrout Plus is approved for grout joints ranging from 1/16" to 1/2" (1.5 mm to 13 mm) in width, eliminating the need for different grout products.

STANDARDS:

- Exceeds ANSI A118.7

COVERAGE				
PROGROUT PLUS/INTEGRA/DURACOLOR PER 25-LB. BAG				
NOMINAL TILE SIZE	JOINT WIDTH			
	1/8"	1/4"	3/8"	1/2"
2"x 2"x 1/4"	93	48	33	26
4"x 4"x 3/8"	122	62	42	32
4"x 8"x 3/8"	162	82	55	42
6"x 6"x 3/8"	182	92	62	47
6"x 8"x 3/8"	208	105	70	53
8"x 8"x 3/8"	242	122	82	62
10"x 10"x 3/8"	302	152	102	77
12"x 12"x 3/8"	362	182	122	92
15"x 15"x 3/8"	452	227	152	114
16"x 16"x 3/8"	482	242	162	122
18"x 18"x 3/8"	542	272	182	137
20"x 20"x 3/8"	602	302	202	152

USES

- Ceramic tile and natural stone applications
- Floors and walls
- Residential and commercial
- Interior and exterior

ORDERING INFORMATION

Color	Sanded 25 lbs.
BRIGHT WHITE	2573-00010
SNOW WHITE	2573-00011
NAVAJO WHITE	2573-00012
CREAM	2573-00018
CANVAS	2573-00021
TUMBLEWEED	2573-00025
SILVER	2573-00030
LIGHT TAUPE	2573-00032
RIVER ROCK	2573-00034
NATURAL GRAY	2573-00035
GRAY	2573-00038
SANDSTONE	2573-00071
SANTA FE	2573-00150
BUCKSKIN	2573-00153
TRUE TAUPE	2573-00162
DARK CHOCOLATE	2573-00175
TERRACOTTA	2573-00191
BLACK SAPPHIRE	2573-00525

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424