



SLU PRIMER



- ◆ INCREASES BOND STRENGTH
- ◆ INHIBITS RAPID WATER LOSS
- ◆ INSTALLER FRIENDLY



SLU PRIMER

SLU PRIMER is a uniquely formulated emulsion applied to all substrates prior to the application self-leveling underlayment. SLU Primer primes and seals floors to increase bond strength and prevent rapid water loss.

SUITABLE SUBSTRATES:

- Mortar Beds
 - Ceramic Tile & Stone
 - Concrete
 - Concrete masonry
 - Exterior-grade plywood¹
- ¹ Interior use only

USES:

- Prepare uneven concrete or exterior-grade plywood floors for leveling
- Ready substrates for smoothing rough and spalled concrete
- Improves self-leveling for large format tile installations

SUITABLE FLOORING TYPES:

- Carpet
- Wood/Laminate
- VCT
- Sheet vinyl
- Pavers
- Stone

APPROXIMATE COVERAGES

Substrate	Coverage per Gallon
Concrete	600 sq. ft.
Plywood; existing tile	250 - 300 sq. ft.

ORDERING INFORMATION

Item#	Size
1883	1-Gallon Bottle

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424