



UNDERLAY SLU

SELF-LEVELING
UNDERLAYMENT



UNDERLAY
SLU
CEMENTITIOUS
SELF-LEVELING
UNDERLAYMENT

- Quick-Setting
- Ideal for leveling from featheredge to 3/4" thickness
- Installer friendly
- Minimal labor required

50 LBS | 22.67 KGS

PAREXUSA

- ◆ FAST SETTING
- ◆ INSTALLER FRIENDLY
- ◆ FEATHER EDGE TO 3/4" THICKNESS
- ◆ 4,100 PSI HARDNESS — PERFECT FOR RETAIL AND LIGHT COMMERCIAL



UNDERLAY SLU

UNDERLAY SLU is a pourable, pumpable and free-flowing Portland-cement-based underlayment for rapid leveling interior substrates. SLU can be poured from featheredge to $\frac{3}{4}$ " thickness in one pour. Underlay SLU is specifically formulated to smooth out and level substrates with excellent durability for the installation of all floor coverings.

SUITABLE SUBSTRATES:

- Mortar Beds
 - Ceramic Tile & Stone
 - Concrete
 - Concrete masonry
 - Exterior-grade plywood^{1 2}
- ¹ Interior use only
² With use of metal lath

USES:

- Leveling uneven concrete or exterior-grade plywood floors
- Smoothing rough and spalled concrete
- Self-leveling for large format tile installations

SUITABLE FLOORING TYPES:

- Carpet
- Wood/Laminate
- VCT
- Sheet vinyl
- Pavers
- Stone

APPROXIMATE COVERAGES

Thickness in Inches	Coverage
$\frac{1}{4}$ "	25 sq. ft.
$\frac{1}{8}$ "	50 sq. ft.

ORDERING INFORMATION

Item#	Size
1886	50-lb. bag

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424