## COLORED CAULKING

- Maximum joint width and depth should not exceed 1/4"
- Designed for use around tubs and sinks with sanded grout
- Used where horizontal and vertical surfaces meet
- Available in sanded and smooth

## MK 100% SILICONE CAULK

- For interior and exterior use with tile or stone
- Flexible material for use on expansion joints
- Suitable for wet and submerged areas
- ASTM C920 / C794

## REVIVE

- Water-based urethane acrylic grout stain and sealer
- For revitalizing or changing color of older sanded or non-sanded grouts
- Designed to help protect against moisture and staining

## GROUT SEALER

- Penetrating silicone sealer suitable for porous, absorbent masonry, clay, stone, marble and portland cement grouts
- Water-based silicone resin designed to protect grout surfaces from stains and water

## BURST

- Powerful easy-to-use additive that accelerates set time
- Does not affect grout performance characteristics
- Excellent for repair work



Merkrete Grout Solutions

# COVERAGE CHARTS

## PROGROUT PLUS / INTEGRA / DURACOLOR

Per 25-lb. Bag

| | JOINT WIDTH | | | |
|---|---|---|---|---|
| NOMINAL TILE SIZE | 1/8" | 1/4" | 3/8" | 1/2" |
| 2" x 2" x 1/4" | 93 | 48 | 33 | 26 |
| 4" x 4" x 3/8" | 122 | 62 | 42 | 32 |
| 6" x 6" x 3/8" | 182 | 92 | 62 | 47 |
| 8" x 8" x 3/8" | 242 | 122 | 82 | 62 |
| 12" x 12" x 3/8" | 362 | 182 | 122 | 92 |
| 16" x 16" x 3/8" | 482 | 242 | 162 | 122 |
| 18" x 18" x 3/8" | 542 | 272 | 182 | 137 |
| 20" x 20" x 3/8" | 602 | 302 | 202 | 152 |

## DURACOLOR Non-Sanded

Per 10-lb. Box

| | JOINT WIDTH | | |
|---|---|---|---|
| NOMINAL TILE SIZE | 1/16" | 3/32" | 1/8" |
| 1" x 1" x 1/4" | 53 | 36 | 27 |
| 2" x 2" x 1/4" | 103 | 69 | 53 |
| 4" x 2" x 1/4" | 137 | 92 | 69 |
| 4" x 4" x 3/8" | 137 | 92 | 69 |
| 4" x 8" x 3/8" | 182 | 122 | 91 |
| 6" x 6" x 3/8" | 205 | 137 | 103 |
| 8" x 8" x 3/8" | 272 | 182 | 137 |
| 12" x 12" x 3/8" | 408 | 272 | 205 |

## ELITE READY-TO-USE GROUT

Per 1-Gallon Unit

| | JOINT WIDTH | | | | | |
|---|---|---|---|---|---|---|
| NOMINAL TILE SIZE | 1/16" | 1/8" | 3/16" | 1/4" | 3/8" | 1/2" |
| 1" x 1" x 1/4" | 103 | 50 | 33 | 24 | 15 | 11 |
| 2" x 2" x 1/4" | 221 | 109 | 72 | 54 | 35 | 26 |
| 4" x 2" x 1/4" | 313 | 155 | 103 | 77 | 50 | 37 |
| 4" x 4" x 3/8" | 278 | 138 | 91 | 68 | 45 | 33 |
| 4" x 8" x 3/8" | 417 | 208 | 138 | 103 | 68 | 50 |
| 6" x 6" x 3/8" | 334 | 166 | 110 | 82 | 54 | 40 |
| 8" x 8" x 3/8" | 557 | 278 | 184 | 138 | 91 | 68 |

## PRO EPOXY

Per 1-Gallon Unit

| | JOINT WIDTH | | |
|---|---|---|---|
| NOMINAL TILE SIZE | 1/8" | 1/4" | 3/8" |
| 6" x 6" x 3/8" | 106 | 58 | 40 |
| 6" x 6" x 1/2" | 80 | 42 | 28 |
| 8" x 8" x 3/8" | 142 | 72 | 58 |
| 12" x 12" x 3/8" | 210 | 106 | 72 |
| 12" x 12" x 1/2" | 156 | 80 | 54 |
| 12" x 12" x 5/16" | 84 | 42 | 28 |
| 16" x 16" x 3/8" | 280 | 142 | 96 |
| 18" x 18" x 3/8" | 312 | 156 | 106 |
| 20" x 20" x 3/8" | 344 | 176 | 118 |

Coverages are approximate and may be reduced based on project conditions, actual tile size, waste and other factors. Please reference Merkrete's Grout Calculator for other tile sizes and more details.

**PAREX**USA
Parex USA Inc., A California Company
2150 Eastridge Ave.
Riverside, CA 92507
www.parexusa.com
886-516-0061
Tech Support: 800-226-2424
©2022, Parex USA, Inc. MK G CC 1222

# GROUT COLOR COLLECTION

# PRODUCT SELECTION

## ELITE READY-TO-USE GROUT

- Superior performance
- Color consistent with no efflorescence
- Easy to spread and clean
- No sealing required
- For grout joints 1/16" to ½" wide

## PROGROUT PLUS

- High-performance, fast-setting grout for joints 1/16" to 1/2" wide
- Color consistent
- Stain resistant and efflorescence free
- Exceeds ANSI A118.7

## DURACOLOR

- Available in sanded and non-sanded
- Sanded for 1/8" to 1/2" grout joints
- Non-sanded For grout joints up to 1/8"
- Polymer fortified for hard, durable, professional results
- Stain resistant and color consistent
- Exceeds ANSI A118.6

## INTEGRA

- Non-abrasive all-in-one thin set and grout
- Color consistent – thinset and grout are the same color
- Specifically designed for glass and mosaic tiles on floors and walls

## PRO EPOXY

- Chemical and stain resistant
- Color consistent; easy to use
- Exceeds ANSI A118.3

# GROUT
## COLOR SELECTION

Tile size, style, color, composition and areas of use constantly evolve. So must the tile installation products. Using the correct installation products is vital to the success of every tile project and selecting the right grout is just as important.

# GROUT CALCULATOR
www.merkrete.com/grout_calculator.shtml

All colors available in Duracolor Sanded and Non-Sanded, Colored Caulking and Revive. **PGP** ProGrout Plus **PE** Pro Epoxy **I** Integra **SC** 100% Silicone Caulk **E** Elite

00010 BRIGHT WHITE **PGP SC**

00011 SNOW WHITE **PGP I SC E**

00012 NAVAJO WHITE **PGP PE SC E**

00015 SWISS COFFEE **I**

00017 BONE **PE I**

00018 CREAM **PGP PE SC E**

00021 CANVAS **PGP PE SC E**

00023 LATTE

00024 CHAMOIS **PE**

00025 TUMBLEWEED **PGP PE I SC E**

00030 SILVER **PGP PE I SC E**

00032 LIGHT TAUPE **PGP PE SC**

00034 RIVER ROCK **PGP PE SC E**

00035 NATURAL GRAY **PGP PE SC E**

00038 GRAY **PGP PE I SC E**

00057 HARVEST

00063 CARMEL **PE**

00134 NEW ADOBE

00137 AZTEC

00162 TRUE TAUPE **PGP PE SC**

00175 DARK CHOCOLATE **PGP SC E**

00178 COCO **PE**

00525 BLACK SAPPHIRE **PGP PE I SC E**

00572 NEW DENIM

00583 ANCIENT JADE

00071 SANDSTONE **PGP PE SC E**

00145 MOCHA **PE**

00147 ESPRESSO

00150 SANTA FE **PGP PE SC E**

00153 BUCKSKIN **PGP PE I SC E**

00191 TERRACOTTA **PGP SC PE**

Sample colors shown are approximate to the final grout color. Final installed grout color may vary due to job conditions, tile porosity, mixing ratio, sealers, installation methods, temperature, or individual batches. Use grouts with the same batch number whenever possible. Different batch numbers should be dry blended together to obtain color uniformity. Follow ANSI A108.10 grouting practices. Please contact Customer Care Department for further questions at 877-547-8822.