



REVIVE

GROUT STAIN AND SEALER

- Water-based urethane acrylic grout stain and sealer
- For revitalizing or changing color of older sanded or non-sanded grouts
- Protects against moisture and staining



1. Product Name

Grout Sealer

2. Manufacturer

ParexUSA, Inc.
4125 E. La Palma Ave, Suite 250
Anaheim, CA 92807
866-516-0061
www.merkrete.com

3. Product Description

Basic Use

Merkrete Revive is a pigmented, water-based urethane acrylic grout stain and sealer.

Features

For revitalizing or changing color of older sanded or non-sanded grout. Revive is designed to help protect against moisture and staining.

Shelf Life

Reference Parex USA Expiration Date of Products Technical Bulletin.

4. Technical Data

Do not use Revive for underwater applications (e.g., pools, tubs, sinks, etc.). Do not use when temperatures are below 40° F or above 110° F. Do not allow container to freeze or get above 110° F. Avoid scrubbing newly applied stain for 20 days. Method of application and grout porosity will vary coverage. Wear proper gloves and eye protection. Do not take internally. If ingested, do not induce vomiting. Seek medical attention. If contact with eyes or skin occurs, flush with water. If irritation persists, seek medical attention.

5. Installation

Before attempting to color your grout with Revive, test a small area first. Test for previously applied sealers by applying a few drops of water on the grout joint. If the water beads, a sealer is present and must be removed before application of Revive. New grout: Allow no less than seven days curing time before application of Revive. All grouts: Surface must be dry, free of oil, grease, dirt, sealers, or any other contaminant. Protect porous tiles to ensure the grout stain does not penetrate into the tile. Shake well before using. Pour a small amount of Revive into a container. Using a bristle or sponge brush, dip into stain and apply a thin coat to grout joint using a back and forth motion. Try to limit the amount of stain on the tile. Wipe off excess immediately with a damp terry cloth towel. Two or more application may be required depending on grout porosity and color. Allow two hours between coats.

4 x 4 tile x 1/4" joint = Approx. 80 sq. ft.

6 x 6 tile x 1/4" joint = Approx. 90 sq. ft.

12 x 12 tile 1/4" joint = Approx. 125 sq. ft.



6. Availability

30 Colors in 8-oz. bottles. Merkrete Revive is available at leading tile houses and construction distributors. Contact Merkrete or visit our website for the name of the nearest dealer at www.merkrete.com.

7. Warranty

Merkrete warrants that this product meets applicable ANSI standards in force at the time of manufacture. Merkrete will replace any product which proves defective due to quality of ingredients used or to the manufacturing process itself. The warranty shall apply only if the product is installed and used strictly in accordance with applicable industry standards, specifications and instructions provided by Merkrete. Merkrete shall not be liable for misapplication, misuse or abuse of the product, or other event outside of its control. Replacement of defective product or, at Merkrete's option, refund of the price of product for any defective item shall be the buyer's sole remedy under this warranty. Merkrete shall in no event be liable for any damages in excess of the purchase price of the defective product. MERKRETE SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES. This warranty constitutes the sole and exclusive warranty given by Merkrete in connection with this product, and Merkrete has authorized no person to make or give any other warranties or representations, oral or written, on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION, WARRANTIES, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification of this warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Merkrete.

8. Maintenance

Avoid scrubbing newly applied stain for 20 days. Do not use harsh cleaners. Mild soap and water should be all that is required.

9. Technical Services

Merkrete Systems maintains technical field representatives available throughout the country. Call Technical Services at 800-226-2424 for the nearest representative.

10. Filing Systems

Merkrete architectural product information available either in catalog form or electronically on our website at www.merkrete.com.



Corporate Office
2150 Eastridge Ave
Riverside, CA 92507

www.merkrete.com
866-516-0061

Tech Support: 800-226-2424